


FAIRBANKS®

OMNICELL® 9101 FB SERIES WEIGHING ASSEMBLY



Fairbanks' Omnicell 9101 FB Series is a cost-effective choice for low-capacity, indoor, commercial, and non-commercial weighing applications. Capacities ranging from 500 to 2,500 pounds are NTEP and FM approved.

APPLICATIONS

- Tanks
- Bins
- Blending
- Mixing
- Batching
- Conveyor
- Low capacity
- Hoppers

FEATURES


- Low profile design
- Low-to-medium weight range — 100 to 2,500 lbs.
- Stainless steel mounting hardware.
- Stainless steel load cell — 100 to 250 lb. models.
- Nickel-plated alloy steel load cell — 500 to 2,500 lb. models.
- Environmentally protected load cells.
- Neoprene isolation/compression mount provides for shock absorption, thermal expansion and contraction and compensates for minor misalignment.
- Custom capacities and cable lengths available.

DIMENSIONS (in inches)

Capacity	A	B	C	D	E	F	G	H	I	J	K	L	TYPE
100 lbs to 250 lbs	4.00	3.14	3.00	0.37	3.25	2.25	3.88	3.00	0.50	0.25	2.38	0.35	Y
500 lbs	6.00	3.88	4.00	1.00	4.00	3.00	5.50	4.13	0.50	0.25	3.38	0.47	Y
1,000 lbs	6.00	4.00	4.00	1.00	4.00	3.00	5.13	4.13	0.50	0.25	3.00	0.47	X
2,500 lbs	6.00	4.00	4.00	1.00	4.00	3.00	6.25	5.00	0.50	0.38	4.62	0.56	X

PERFORMANCE SPECIFICATIONS

Capacities	100 to 2,500 lbs.
Mount Construction	Stainless steel
Load cell:	
Full Scale Output (FS)	3.0mV/v $\pm$ 0.25%
Combined Error	$\leq$ 0.03% FS
Non-Linearity	$\leq$ 0.03% FS
Hysteresis	$\leq$ 0.02% FS
Creep Error (20 min.)	$\leq$ 0.03% FS
Compensated Temperature	14° F to 104° F (-10° C to 40° C)
Excitation Voltage	5-15 VDC
Overload	Safe = 150% Ultimate = 300%
Sideload	Safe = 100%
Rejection ratio	500:1
Bridge Resistance	350 ohms nominal
Construction	Stainless steel Nickel-Plated alloy steel
Sealing	IP67
Approvals	NTEP CC# 12-028 and Factory Mutual on capacities 500 lbs. and greater.



The style of the isolation mount changes with the capacity.

CABLE
COLOR CODE
RED=+EX
BLACK=-EX
WHITE=-SIG
GREEN=+SIG

QuickFacts™

Models and specifications subject to change without notice.
Printed in the USA. © Fairbanks Scales Inc.

Call toll-free for the Fairbanks representative nearest you:

(800) 451-4107

Fairbanks.com

01/24 100302