## FAIRBANKS® SCALES




# TALON HV & HVX SERIES ABOVEGROUND FIELD POUR TRUCK SCALES


Built on a proven orthotropic design, the Talon boasts the longest-lasting construction of any field pour truck scale in the industry.

## TALON HV HVX FIELD POUR

Experience a scale like no other. The Fairbanks Talon Field Pour boasts the longest-lasting construction of any truck scale in the industry. Built on a proven orthotropic design, the Talon has numerous design achievements that stand out over the competition. With tens of thousands of Fairbanks truck scales sold to date, the Talon is sure to be a great addition to your weighing system.







By placing the load cells in easily accessible and serviceable areas beneath the scale, instead of inside the deck, Fairbanks has eliminated the need for cover plates. This design ensures a more structurally sound scale deck that resists metal fatigue, deflection, and internal deck cracks.



12' wide decks are available. Extra deck width accommodates larger trucks and equipment, and ensures easier scale navigation.

## THE NEXT GENERATION IN TRUCK SCALE DESIGN

Solid Deck Design

Intalogix® Technology

**Encapsulated Circuit Boards** 

Incredibly strong modules, built to federal bridge standards

Cabling protected with ArmourGuard stainless steel sheathing

"True" hermetically sealed Minebea Intec load cells

Easy installation and maintenance

Legal-for-trade dumpthrough modules have an all-steel design and are available in custom sizes and placements.





Paint for all exposed metal scale components is a chemically crosslinked, two-component, acrylic urethane industrial coating system that stands up to wear.



INTALOGIX TECHNOLOGY

This innovative design feature isolates and guards your scale investment against power surges and dangerous electrical strikes.



**Sectional controllers** optically isolate load cells, providing the best surge and lightning protection available.



Encapsulated circuit boards provide the best protection in the industry against moisture damage. Our encapsulating material was first used in aerospace applications.



Minebea Intec rocker column load cells

have true hermetic seals to prevent moisture intrusion and are electrochemically polished to retard corrosion in the most caustic environments.

## TALON HV & HVX SERIES ABOVEGROUND FIELD POUR TRUCK SCALES

**Weighing Solutions for the World Since 1830** 

Fairbanks.com

#### **SPECIFICATIONS**

60 ton to 150 ton (HVX)

CLC ..... 90 k (HV) 100 k (HVX)

Platform sizes

Custom lengths available

Sections . . . . . . . . . . . . . . . . . 2 to 7 Modules . . . . . . . . . . . . . . . . . . 1 to 6

Module data:

Design . . . . . Orthotropic

HVX features multiple 6" and 12" I-beams

With 1/4" support pan

Filled with on-site poured concrete

Under structure..... Open bottom Deck thickness . . . . . . . . . . . . . . . . . 10" (HV)

12" (HVX)

Cover plates . . . . . . . . . No Checking. . . . . . . . . . . . . . . Bumper

Approvals . . . . . . . . . . . . NTEP CC# 96-089,

MC# AM-4949

Load cell:

Height . . . . . . . . . . . . . . . . . . 4.66"

110,000 lbs (HVX)

Type . . . . . Rocker column

Sealing . . . . . . . . . . . . . Welded, hermetically sealed,

gas filled

Material..... Element - 420

Can - 304

Rating . . . . . IP69K Resistance . . . . . . . . . . . . . . . . 1,000 ohms Excitation . . . . . . . . . . . 4 to 24 VDC Ultimate overload . . . . . . . . . . . . 300% Cable length . . . . . . . . . . . . . . . . . 15'

Cable protection . . . . . . . . Stainless steel braid ArmourGuard Approvals . . . . . . . . . . . NTEP CC# 14-024, Factory Mutual,

CE. OIML R60/2000-DE-08.11

### **ACCESSORIES**

Scale Instruments



Remote Displays



Ticket printers

Traffic Signals





**Driver Assist Terminals** 









#### **OPTIONS**

Blow-down plates Custom sizes Dress plates Drop plates Dump through deck Coal Tar undercoating Guide post kits Intrinsically safe electronics Load cell riser plates

Rub rails

Manholes (square)

Your Fairbanks Scales Authorized Representative is:

Call toll-free for the representative nearest you:

(800) 451–4107

Call between 8:00 a.m. - 5:00 p.m. Central Time Corporate Headquarters: 6800 W. 64th Street, Overland Park, Kansas 66202 (816) 471-0231 Internet Address: http://www.Fairbanks.com

